

## Technical Data: Flex<sup>e</sup>Port Spring Arms

Type	Flex <sup>e</sup> Port 20	Flex <sup>e</sup> Port 30	Flex <sup>e</sup> Port 40
Model	Ceiling and wall mounted	Ceiling and wall mounted	Ceiling and wall mounted
<b>Load max.</b>	1.5-3.5 / 3.5-7 / 3-6 / 7-12 / 8-13 / 9-15/12-18 / 13.5-21 kg	7-11 kg / 12-18 kg / 17-30 kg	8-15 kg / 15-32 kg / 30-40 kg
<b>Features</b>	adjustable upper motion limit, exact parallel guidance, comfortable weight adjustment, rotational stop	Rotational stop	Rotational stop
<b>Cable routing</b>	2 cables of each max. $\varnothing$ 9mm	384 mm <sup>2</sup> 1 cable $\varnothing$ 9 mm plus 1 cable $\varnothing$ 6 mm plus 2 cables each $\varnothing$ 5 mm	450 mm <sup>2</sup> 2 cable each $\varnothing$ 12 mm plus 2 cables each $\varnothing$ 6,5 mm
<b>Colours</b>	RAL 9002, 9010	RAL 9002, RAL 9010	RAL 9002, RAL 9010
<b>Certificates</b>	CE, UL	VDE, CE, UL	VDE, CE, UL

